

## What is Grab?

GRAB is a powerful, low odour product that dissolves ink and paint graffiti from any hard surface subject to graffiti, except aluminium.

### Key Benefits

- ✓ Dissolves ink and paint
- ✓ Low odour
- ✓ Clings to vertical surfaces
- ✓ Rinses away with water

## How Does It Work?

GRAB is a very powerful solvent-type paint and ink removal agent. It is water-emulsifiable so it can be rinsed away effectively with water. It is a low odour liquid with outstanding performance and it is a thickened liquid so it will "cling" to vertical surfaces. GRAB will not leave unwanted chemical odours after being used. It is classified as Dangerous Goods.

## For Use On...

GRAB quickly and thoroughly dissolves aerosol paint, felt-tipped pen ink, ballpoint pen ink and other graffiti from stone, fibreglass, concrete and brickwork. It is ideal for use on walls and brickwork, and other surfaces subjected to graffiti. It should not be used on painted surfaces, soft furnishings or aluminium metal.

## Caution

Use caution before applying GRAB to soft vinyl or plastic. It is advisable to pre-test the product on unknown or sensitive surfaces to ensure no damage will occur. Avoid spilling the product on paintwork, shoes and furniture. Wear solvent-resistant gloves (nitrile or neoprene) to prevent skin contact. Do not leave the product lying around after use. Also, avoid using food containers for storing the products. Read the SDS for GRAB and observe all safety precautions.

## Technical Data

### Properties



COLOUR – Hazy brown liquid  
ODOUR – Solvent  
pH = 13 – 14  
FOAM – Low foam height

## Dangerous Goods Classification:

GRAB is a Class 3 flammable and Class 8 Corrosive Liquid.

U.N. No: 2924	CLASS: 3, 8
PACK GRP: III	HAZCHEM: 3W

## Environmental Care

GRAB conforms with all statutory environmental requirements. It is based on powerful ingredients selected to perform efficiently so there is no waste or damage. GRAB containers will be cleaned and reused if returned to Agar Cleaning Systems Pty Ltd., significantly reducing plastic usage and waste. They can also be recycled.

## Quality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 "Quality Management Systems – Requirements".

First Certified: 30 April 1996 SAI Certificate No.: QEC7358

## Application

Graffiti is easiest to remove when it is fresh, so act promptly.

GRAB is not suitable for use on aluminium or painted surfaces because it will strip the paint. To remove graffiti from painted walls or aluminium surfaces, use DLX or GRAFFITI WIPE OFF.

### Concrete or Brick:

1. Wear gloves and safety glasses.
2. Use a stiff nylon or wire brush.
3. Brush a thick, uniform coat of GRAB onto the graffiti.
4. Scrub for a minute with brush to assist penetration. Smooth over then leave to work for at least 3 minutes.
5. Apply a second coat of GRAB, repeat steps 3 and 4.
6. Apply a third coat of GRAB, repeat steps 3 and 4.
7. 3 minutes after the last application, rinse off using a hot or cold pressure washer at low pressure. Otherwise, rinse with clean water and brush.
8. Repeat this process if necessary, until the graffiti is gone.

### Metal, Fibreglass, Tiles, Glass:

- Repeat the steps for *Concrete or Brick* but instead use a Soft Brush that will not scratch the surface.

## Storage

GRAB is stable for 12 months. Store in the original sealed container and keep out of direct sunlight. Also avoid storing the product in extremes of temperature; try to keep it between 10 and 30 degrees Celsius.

## Disposal Information

### 1. Used solutions -

Used Solutions of GRAB should be poured into a drain or trough that leads to the sewer system or a septic tank. These systems have a method for treating and breaking down the waste. Used solutions of detergent should not be poured into stormwater drains or down driveways as these drains are designed for rainwater and ultimately lead to the local river system.

### 2. Unused product

It is best to keep the product and use it up! If this is not possible, try to give it to someone who can use it. (Make sure the product is in its original, labelled container).

If there is no alternative but disposal, it is safe to pour modest quantities of this product down the drain (to sewer) with running water. Leave the cold tap running for a few moments afterwards as this dilutes the product and reduces the concentration in the wastewater.

Remember, do not mix different cleaning products together during disposal!

### Cardboard cartons

Used boxes should be flattened and recycled in OCC (old, corrugated cardboard) or mixed wastepaper recycling programs.

Available in: 5L

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.



**MELBOURNE**  
Agar Cleaning Systems P/L  
12-14 Cope Street  
Preston VIC 3072  
Ph: (03) 9480 3000

**ADELAIDE**  
Agar Cleaning Systems P/L  
Unit 1, 138-140 Ashley Street  
Underdale SA 5032  
Ph: (08) 8293 2020

**BRISBANE**  
Agar Cleaning Systems P/L  
Unit 5, 13 Murdoch Circuit  
Acacia Ridge QLD 4110  
Ph: (07) 3274 3438

**SYDNEY**  
Agar Cleaning Systems P/L  
Unit 3, 68-72 Asquith Street  
Silverwater NSW 2128  
Ph: (02) 9743 6020

**PERTH**  
Briskleen Supplies  
38 Mulgool Road  
Malaga WA 6090  
Ph: (08) 9249 4566